**Product information** 

# ANCAMIDE® 3033

# **Curing Agent**

# **DESCRIPTION**

Ancamide 3033 curing agent is a low viscosity amidoamine.

The curing agent is a longer pot life variant of Ancamide 3032 curing agent and is recommended for use with liquid epoxy resin for the development of epoxy mortars and casting resins with a long pot life and good physical properties.

# **TYPICAL PROPERTIES**

Property	Value	Unit	Method
Appearance	Clear amber liquid		
Colour	≤ 10	Gardner	ASTM D 1544-80
Viscosity @ 25°C	80-400	mPa.s	Brookfield RVTD, Spindle 4
Amine Value	370-410	mg KOH/g	Perchloric Acid Titration
Specific Gravity @ 21°C	0.94		
Equivalent	95	Wt/{H}	
Recommended use Level	50	PHR	With liquid Bisphenol A diglycidyl ether (EEW=190)

# **ADVANTAGES**

- Low viscosity
- Long pot life
- Low exotherm

# **APPLICATIONS**

- Epoxy mortars
- Casting resins

# **SHELF LIFE**

At least 24 months from the date of manufacture in the original sealed container at ambient temperature. Store away from excessive heat and humidity in tightly closed containers.



#### STORAGE AND HANDLING

Refer to the Safety Data Sheet for Ancamide 3033 curing agent.

### TYPICAL HANDLING PROPERTIES

Property	Value	Unit	Method
Gel Time (250g mix at 23°C)	170-180	mins	Techne GT-3 Gelation Timer
Typical cure schedule	2-7	days	

Ancamide® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

#### Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

#### **EVONIK OPERATIONS GMBH**

Business Line Crosslinkers Paul-Baumann-Str. 1 45764 Marl Germany

www.evonik.com/crosslinkers

Sample Request: APCSE@evonik.com Crosslinkers-Samples@evonik.com

#### **EVONIK CORPORATION**

**Business Line Crosslinkers** 7001 Hamilton Boulevard Trexlertown, PA 18087 USA

#### **EVONIK SPECIALTY CHEMICALS** (SHANGHAI) CO., LTD.

**Business Line Crosslinkers** 55, Chundong Road Xinzhuang Industry Park Shanghai, 201108 China

CL-Asiainfo@evonik.com CL-Asiainfo@evonik.com

