

**ANCAMINE<sup>®</sup> 2672****Curing Agent****DESCRIPTION**

Ancamine 2672 curing agent is a modified cycloaliphatic amine designed for use as a room temperature curing agent for liquid epoxy resin. Special features of this curing agent include low viscosity, allowing for higher filler loadings and the ability to cure relatively quickly at low temperatures. Ancamine 2672 curing agent is intended for use in solvent-free coatings, high film build systems, selfleveling and screed flooring applications.

**TYPICAL PROPERTIES**

Property	Value	Unit	Method
Appearance	Clear, amber liquid		
Colour	<8	Gardner	ASTM D 1544-80
Viscosity @ 25°C	100-300	mPa.s	Brookfield RVTD, Spindle 4
Amine Value	280-340	mg KOH/g	Perchloric Acid Titration
Specific Gravity @ 21°C	1.06		
Equivalent	95	Wt/{H}	
Recommended use Level	50	PHR	With Bisphenol A diglycidyl ether (EEW=190)

**ADVANTAGES**

- Good corrosion resistance
- Excellent chemical resistance
- Good resistance to water spotting and amine blush
- Nonyl phenol and bisphenol-A free

**APPLICATIONS**

- Primers, sealers and coatings for concrete
- Chemical resistance tank linings
- High solid coatings
- Non colour sensitive applications

## SHELF LIFE

At least 24 months from the date of manufacture in the original sealed container at ambient temperature. Store away from excessive heat and humidity in tightly closed containers.

## STORAGE AND HANDLING

Refer to the Safety Data Sheet for Ancamine 2672 curing agent.

## TYPICAL HANDLING PROPERTIES \*

Property	Value	Unit	Method
Gel Time (150g mix @ 25°C )	30	mins	Techne GT-3 Gelation Timer
Thin Film Set Time @ 25°C	5	h	BK Drying Recorder Phase II
Typical cure schedule	2-7	days	

## TYPICAL PERFORMANCE PROPERTIES \*

Property	Value	Unit	Method
Persoz Hardness (10 days at 23°C)	300	s	
Heat Distortion Temperature	48	°C	ASTM D648
Carbamation Test	3-4		ISO 2812 (Wet Patch Method), scale 1-5 (5 is best)

\*With Bisphenol A diglycidyl ether (EEW=190)

Ancamine® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

**Disclaimer**

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

**EVONIK OPERATIONS GMBH**

Business Line Crosslinkers  
Paul-Baumann-Str. 1  
45764 Marl  
Germany

[www.evonik.com/crosslinkers](http://www.evonik.com/crosslinkers)

**Product Information:** [APCSE@evonik.com](mailto:APCSE@evonik.com)

**Sample Request:** [APCSE@evonik.com](mailto:APCSE@evonik.com)

**EVONIK CORPORATION**

Business Line Crosslinkers  
7001 Hamilton Boulevard  
Trexlerstown, PA 18087  
USA

[CrosslinkersProinfo@evonik.com](mailto:CrosslinkersProinfo@evonik.com)

[Crosslinkers-Samples@evonik.com](mailto:Crosslinkers-Samples@evonik.com)

**EVONIK SPECIALTY CHEMICALS  
(SHANGHAI) CO., LTD.**

Business Line Crosslinkers  
55, Chungong Road  
Xinzhuang Industry Park  
Shanghai, 201108  
China

[CL-Asiainfo@evonik.com](mailto:CL-Asiainfo@evonik.com)

[CL-Asiainfo@evonik.com](mailto:CL-Asiainfo@evonik.com)

