Product information

ANCAMINE® 3137

Curing Agent

DESCRIPTION

Ancamine 3137 curing agent is a modified cycloaliphatic polyamine intended for use as an ambient curing agent for liquid epoxy resin. Ancamine 3137 curing agent can be used to formulate high solid coatings and solvent free industrial floorings.

TYPICAL PROPERTIES

Property	Value	Unit	Method
Appearance	Clear, light yellow liquid		
Colour	≤ 4	Gardner	ASTM D 1544-80
Viscosity @ 25°C	70-150	mPa.s	Brookfield RVTD, Spindle 4
Amine Value	300-325	mg KOH/g	Perchloric Acid Titration
Specific Gravity @ 21°C	1.06		
Equivalent	95	Wt/{H}	
Recommended use Level	50	PHR	With Bisphenol A diglycidyl ether (EEW=190)

ADVANTAGES

- Fast cure and development of properties at ambient and low temperature
- · Good resistance to carbamation and waterspotting
- Low viscosity

APPLICATIONS

- Chemical resistant high solids and solvent free coatings
- · Industrial flooring applications

SHELF LIFE

At least 36 months from the date of manufacture in the original sealed container at ambient temperature. Store away from excessive heat and humidity in tightly closed containers.



STORAGE AND HANDLING

Refer to the Safety Data Sheet for Ancamine 3137 curing agent.

TYPICAL HANDLING PROPERTIES*

Property	Value	Unit	Method
Gel Time (250g mix at 23°C)	30-35	mins	Techne GT-3 Gelation Timer
Typical cure schedule	2-7	days	

^{*}With Bisphenol A diglycidyl ether (EEW=190)

Ancamine® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

EVONIK OPERATIONS GMBH

Business Line Crosslinkers Paul-Baumann-Str. 1 45764 Marl Germany

www.evonik.com/crosslinkers

Sample Request: APCSE@evonik.com Crosslinkers-Samples@evonik.com

EVONIK CORPORATION

Business Line Crosslinkers 7001 Hamilton Boulevard Trexlertown, PA 18087 USA

EVONIK SPECIALTY CHEMICALS (SHANGHAI) CO., LTD.

Business Line Crosslinkers 55, Chundong Road Xinzhuang Industry Park Shanghai, 201108 China

CL-Asiainfo@evonik.com CL-Asiainfo@evonik.com

