Product information

SUNMIDE® 305-70X

Curing Agent

DESCRIPTION

Sunmide 305-70X is a polyamide amine widely used as a room temperature curing agent of epoxy resins in solvent-based protective coatings. When used with solid epoxy resin, Sunmide 305-70X has good adhesion, high flexibility, long pot life and all around good properties.

TYPICAL PROPERTIES

Property	Value	Unit	Method
Amine Value	170	mg KOH/g	
Non Volatile	70	%	
Viscosity @ 25°C / 77 °F	1300	сР	
Color	6	Gardner	
Specific Gravity	0.94		
Flash point	32	°C	Closed Cup
Solvent	Xylene		
Equivalent Wt/{H}	180		solid
	257		solution

ADVANTAGES

- Ambient cure
- Low toxicity
- Good flexibility and toughness
- · Long pot life
- · Good water and corrosion resistance

APPLICATIONS

- Solvent-based protective coatings, e.g. primers, finishes and coal tar epoxy coatings.
- Industrial maintenance coatings
- Marine coatings

SHELF LIFE

- Stable under temperate or tropical conditions.
- Recommended shelf life 1 year



STORAGE AND HANDLING

Refer to the Safety Data sheet for Sunmide 305-70X curing agent.

TYPICAL FORMULATION RATIO

Epoxy (EEW 230 - 270) / Sunmide 305-70X = 100 / 72 Epoxy (EEW 450 - 500) / Sunmide 305-70X = 100 / 38

Sunmide® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

Disclaimer

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-IMFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

EVONIK OPERATIONS GMBH

Business Line Crosslinkers Paul-Baumann-Str. 1 45764 Marl Germany

www.evonik.com/crosslinkers

Sample Request: APCSE@evonik.com Crosslinkers-Samples@evonik.com

EVONIK CORPORATION

Business Line Crosslinkers 7001 Hamilton Boulevard Trexlertown, PA 18087 USA

EVONIK SPECIALTY CHEMICALS (SHANGHAI) CO., LTD.

Business Line Crosslinkers 55, Chundong Road Xinzhuang Industry Park Shanghai, 201108 China

CL-Asiainfo@evonik.com CL-Asiainfo@evonik.com

